

TP-2510 BEARING GEL

General Purpose BEARING GEL

Tom-Pac® TP-2510 General purpose grease suitable for most service with temperature range of -5°F to 200°F. Suitable for replacement of other GP and MP greases where a stable, water resistant grease is desired. Contains all necessary EP, anti-rust, anti-wear additives required for general service.

● EP ● NON-MELTING ● WATER RESISTANT

Characteristics & details

- non organic, highly stable grease. Resists separation and melting.
- EP, anti wear, anti scuff additives
- Excellent water wash results

Benefits:

Non-melting formula - Gel stays on intended surfaces. Normal grease will melt and drip out of the applications in high temperature conditions; more grease must be added to the application to keep it lubricated. Since TP-2510 will not melt, it amounts to dramatically less lubricant usage and longer lubrication intervals. This amazing characteristic also helps prevent bearing and machinery failure from insufficient lubrication.

Excellent Water Resistance - Frequently, applications are exposed to conditions where water can cause the grease to be washed off. This will leave the intended surface without protection from wear and corrosion. TP-2510 is formulated to resist water drips, sprays and high moisture conditions. It will not break down or emulsify in the presence of water and will hold fast to metal surfaces under pressure.

Extreme Pressure / High Load Protection- TP-2510 combines the most efficient additives to deliver outstanding protection in applications exposed to high load and extreme pressure conditions. Anti-wear and anti-friction additives help machinery run smoother and quieter, while also reducing premature bearing and machinery failure.

Versatility - Most greases are targeted at one specific application and fall short when operating under other conditions. Possibly the most distinguishing benefit that TP-2510 delivers is its ability to operate in a wide spectrum of applications

SPECIFICATIONS

| Description | Value | ASTM Method |
|-------------------------------|--------------|-------------|
| Recommended Temperature Range | 0°F to 200°F | |
| Timken OK Load | 55 lbs | D2509 |
| Flashpoint (base oil) | 225°C | D92 |
| Wear Characteristics - 4 Ball | 0.64 mm | D2266 |
| Water Washout Characteristics | 0.0 g | D1264 |

Available Sizes: TP-2510 is available in 14.1 oz cartridges 120 lb and 400 lb steel drums.

www.tom-pac.com

Notice: All statements in this brochure are based on general service experience. Because of the wide variety of applications and wide range of equipment conditions encountered, together with the unpredictable human factors involved in the installation of this product by the ultimate user, TOM-PAC Inc. makes no warranties expressed or implied, that the product described is guaranteed for any length of time, for any measure of service, or for any specific purpose.

©TOM-PAC INC. 2016, Printed in Canada

Tom-Pac®